

(ATP)

Adjustable Training Platform

The industry's first push-button freestanding adjustable climbing walls from the forthcoming VS Optimatrix series of training products.

Product Overview

- Fully freestanding or anchored installation
- 8'w x 12'h standard, custom sizes optional
- 3/4" thick single layer design
- Hydraulically actuated with dual rams
- Vertical to 50° overhung in seconds
- Built to fit any popular training system (Moon, Tension, Kilter, Lattice, etc.)
- Professionally installed by The VS Team

NEW Financing Available!

- Application-only financing available
- Rates as low as 6%, terms ranging from two to seven years
- Non-personal guaranty financing available
- Approval as quick as 24 hours



Specifications

Construction	Anchored or freestanding steel structure with CNC'd single-layer wood panels
Assembled Weight (w/o holds, appx.)	1650 lbs
Angle Adjustability	0° vertical - 50° overhung
Angle Control	Momentary-action pilot switches on dual hydraulic rams
Angle Feedback	Digital LCD display @ .1° resolution
Electrical Requirements	110v 20 amp circuit
Frame Color	Bare steel; black or custom powdercoating available
Surface Appearance	Baltic birch panels; custom hardwood available
Training Systems Supported	Moon, Lattice, Tension, Kilter, any custom system, + more
Climbing Surface Size	8' x 12' standard, custom sizes available
Kicker Panel Height	24" - 36"
Max Height	15' - 7.25"
Fall Zone @ Vertical	8' from kicker panel
Fall Zone @ 50°	14' from kicker panel
Footprint of Assembled System	12" (W) x 17'3" (L)
Pad Specification	12" Habit Flooring ballistic nylon system
Warranty	1 year on all materials and construction

Construction Views (8' x 12' shown)

